International® 530E Diesel Engines

Equipped with
International[®] Diamond Logic™
Engine Control Module

For 1999 through 2003 Model Year Truck and Derivative Vehicle Applications

Engine Operation and Maintenance Manual

© 2010 Navistar, Inc



Scheduled (Normal) Maintenance Will

"Protect Your Investment"

Through Increased Equipment Reliability And Availability.

Normal maintenance is necessary to protect the long life built into your vehicle engine. Navistar, Inc. has designed a program to assist you in restricting delays and keep costly repairs to a minimum. This program consists of normal maintenance, scheduled lubrication intervals, adjustments and inspections. This program, when used, will result in reduced "down-time" and minimum repairs. The systematic procedure of lubrication, adjustments and inspection is outlined in the **MAINTENANCE INSTRUCTIONS** Section of this manual.

Instructions for operation, instrumentation, specifications, maintenance, records and troubleshooting are covered by this manual. The instructions are divided into sections to simplify reference to the most important information. The manual must be read completely prior to operating the engine to gain full knowledge of the engine and its correct normal maintenance and operation.





INTRODUCTION

To The Operator	. 1
Safety Precautions	. 1
Publications Ordering Information	. 4
SECTION 1 – GENERAL INFORMATION	
Component Location (Front View)	. 5
Component Location (Left Side View)	
Component Location (Rear View)	
Component Location (Right Side View)	. 8
Introduction:	. 9
International® 530E On-Highway Diesel Engine	. 9
Engine Identification:	
International® 530E Series Diesel Engine Serial Number Locations	. 9
Explanation Of The Serial Number	
Engine and Accessory Nameplates Locations	
Turbocharger Identification (Non Wastegate Version)	
Turbocharger Identification (Wastegate Version)	.15
SECTION 2 – ENGINE SYSTEMS	
General Features	.17
Chassis Mounted Air-to-Air cooler	
SECTION 3 – WARRANTY INFORMATION	
Emission Control Systems Maintenance And Limited Warranty	.19
Federal Emission System Limited Warranty	

California Emission System Limited Warranty. International's® Emission Limited Warranty Coverage. The Emission Limited Warranty Does Not Cover.	21
SECTION 4 - INSTRUMENTS AND INDICATORS	
Instrument Panel. Engine Diagnostics Button. Water Temperature Gauge.	26
Oil Pressure Gauge.	
Change Engine Oil Lamp	29
Air Cleaner Restriction Indicator	30
Air Restriction Indicator Test	31
SECTION 5 - OPERATION	
Before Starting the Engine	33
Precautions	33
Engine Starting	34
Engine Starting	34 35
Engine Starting Starting The Engine Starting The Engine Above -12°C (10°F) Ambient Temperature	34 35 35
Engine Starting Starting The Engine Starting The Engine Above -12°C (10°F) Ambient Temperature Starting The Engine Below -12°C (10°F) Ambient Temperature With Optional Ether Injecto	34 35 35 r37
Engine Starting Starting The Engine Starting The Engine Above -12°C (10°F) Ambient Temperature Starting The Engine Below -12°C (10°F) Ambient Temperature With Optional Ether Injecto Emergency Starting	34 35 35 r37
Engine Starting. Starting The Engine. Starting The Engine Above -12°C (10°F) Ambient Temperature. Starting The Engine Below -12°C (10°F) Ambient Temperature With Optional Ether Injecto Emergency Starting. Operating Instructions.	34 35 37 40 41
Engine Starting. Starting The Engine. Starting The Engine Above -12°C (10°F) Ambient Temperature. Starting The Engine Below -12°C (10°F) Ambient Temperature With Optional Ether Injecto Emergency Starting. Operating Instructions. Cold Weather Operation.	34 35 37 40 41
Engine Starting. Starting The Engine. Starting The Engine Above -12°C (10°F) Ambient Temperature. Starting The Engine Below -12°C (10°F) Ambient Temperature With Optional Ether Injecto Emergency Starting. Operating Instructions. Cold Weather Operation. Hot Weather Operation.	34 35 r37 40 41 41
Engine Starting. Starting The Engine. Starting The Engine Above -12°C (10°F) Ambient Temperature. Starting The Engine Below -12°C (10°F) Ambient Temperature With Optional Ether Injecto Emergency Starting. Operating Instructions. Cold Weather Operation. Hot Weather Operation. Extended Idling Periods.	34 35 r37 40 41 41 42
Engine Starting. Starting The Engine. Starting The Engine Above -12°C (10°F) Ambient Temperature. Starting The Engine Below -12°C (10°F) Ambient Temperature With Optional Ether Injecto Emergency Starting. Operating Instructions. Cold Weather Operation. Hot Weather Operation. Extended Idling Periods. CAP Shutoff.	34 35 r37 40 41 41 42 42
Engine Starting. Starting The Engine. Starting The Engine Above -12°C (10°F) Ambient Temperature. Starting The Engine Below -12°C (10°F) Ambient Temperature With Optional Ether Injecto Emergency Starting. Operating Instructions. Cold Weather Operation. Hot Weather Operation. Extended Idling Periods.	34 35 r37 40 41 42 42 43

Shutdown Warning Light Or Audible Alarm	44
Parking	44
Road Operation	
Downhill Operation	
Idle Speeds	45
•	
SECTION 6 – SPECIFICATIONS AND CAPACITIES	
Fuel Requirements	51
Recommended Fuel For International® Diesels	51
Advisory	51
Diesel Fuel/Gasoline Blends	52
Hazards Of Fire And Explosion	52
Engine Performance Problems	
Cooling System	53
Requirements	
ROTELLA Extended Life Coolant (Red In Color)	54
Cooling System Specifications	
Maintaining Required Inhibitor Concentration (For Extended Life Antifreeze {Red In Co	lor})55
Coolant Testing For Inhibitor Concentration – (For Extended Life {Red} Coolants)	
Cooling System Requirements – (For Conventional Coolant (Green In Color)	
Ethylene Glycol Antifreeze	
Propylene Glycol Antifreeze	57
Maintaining Required Conditioner Concentration (For Conventional Coolant (Green In	
Coolant Filter/Conditioner	
Coolant Testing For Conditioner Concentration – (For Conventional {Green} Coolant	s)58
Cleaning The Cooling System	
Corrosion Prevention	61
Radiator Fins	
Coolant Hoses	61

ThermostatContamination Of Coolant	62
Engine Lubrication Requirements	
Oil QualityOil Viscosity	
Oil Change Interval.	
Identification Symbol.	
Crankcase Oil Specifications	
International® 530E Series Diesel Engine Crankcase Refill Capacities	
Checking Engine Oil Level	
SECTION 7 MAINTENANCE INSTRUCTIONS	
SECTION 7 - MAINTENANCE INSTRUCTIONS	
General	67
Maintenance Operations	
Maintenance Operations — 1 through 6 Daily Maintenance Schedule	
OPERATION 1 – Check Oil Level (Daily)	
OPERATION 2 — Check Coolant Level (Daily)	
OPERATION 3 — Water Separator, Fuel System - If Equipped (Daily)	
OPERATION 4 — Inspect Air-to-Air cooler (Daily)	
OPERATION 5 — Inspect for External Leakage (Daily)	
OPERATION 6 — Inspect Air Cleaner Restriction Indicator (Daily)	
Maintenance Operations - 7 through 10 Inspection Interval: Every 21,000 km, (13,000	
miles), 500 hours, 6 months or 1,900 gallons of Fuel; Whichever Occurs First	
OPERATION 7 — Inspect Belt	
OPERATION 8 — Change Engine Oil And Oil Filter	
Reset Change Oil Light	
OPERATION 9 — Check Coolant SCA Concentration	
OPERATION 10 — Inspect Air Intake Piping	81

Maintenance Operations – 11 Thru 12 Inspection Interval: Every 48,300 Km (30,000 miles),	
1,100 hours, 12 months Or 4,200 gallons Of Fuel; Whichever Occurs First	82
OPERATION 11 — Measure Air Intake Restriction	82
Optional Dual Element Cleaner	82
OPERATION 12 — Change Fuel Filter And Strainer Assembly	85
Bleeding Air From Fuel System	88
Maintenance Operation —13 Replacement Intervals Depend On Type Of Coolant Used.	
See Section 7, Table 2 For Replacement Interval. Coolant Types Are Extended Life (Red	
In Color) And Conventional (Green In Color)	89
Change Coolant Filter (If Equipped for early 1999 model year)	
Change Coolant Filter (If Equipped For Late 1999 Model Year And Following Years)	
Maintenance Operation — 14 Inspection Interval: Every 24 Months	
Pressurize Induction System	
Maintenance Operation —15 Inspect Vibration Damper	
Inspection Vibration Damper	
Maintenance Operation — 16 Inspection Interval: Annually	
Adjust Valve Lash	
Maintenance Operations 17 And 18 Inespection Interval: Every 290,000 To 322,000 Km	
(180,000 to 200,000 miles), 6,700 To 7,500 hours; Whichever Occurs First	91
OPERATION 17 — Measure Crankcase Pressure	
OPERATION 18 — Inspect Turbocharger	92
Maintenance Operation — 19 Inspection Interval: Annually	
Inspect Electrical System	92
Maintenance Operation — 20 Inspection Interval: Every 322,000 Km (200,000 miles), 3,800	
hours Or 2 Years; Whichever Occurs First	92
Service Cooling System	
For School Bus	94
Clean Cooling System	95
Maintenance Operation — 21 Inspection Interval: Every 500,000 Km (300,000 miles),	
12,000 hours Or 5 Years; Which Ever Occurs First	96

Refer to Section 6: Cooling System Specifications	96
SECTION 8 – SERVICE RECORDS	
Emission Maintenance Service Record. Description.	
SECTION 9 - DAILY MAINTENANCE REPORT	
Daily Care And Report. Description	

